

# Presentation BROL - Grontmij I&M Rail

Aarhus, 09 September 2009


# Summary presentation

- Grontmij
- I&M Rail
- BROL
- What has been done so far
- What still has to be done
- Questions...and conclusion


# Grontmij

Grontmij is a multidisciplinary design, consultancy and engineering firm employing more than 8,000 professionals active in the environmental, water, energy, building, industrial and transportation sectors.


We aim to be the best local service provider in North-West Europe and provide added value throughout the entire process of design, consulting, engineering, contracting and managing multidisciplinary projects.



# Organization structure Grontmij




# Organization structure Grontmij Nederland




# Organization structure Grontmij

## Infra structure & Milieu



# Organization structure department Rail



# Rail services


## Asset based services

- Feasibility *(master planning, business case, EIA's, CBA's)*
- Contracting *(management contracting, EPC, risk based inspection)*
- Design *(life cycle, systems engineering, RAMS)*
- Asset management *(maintenance, monitoring, operation, GIS)*


## Consultancy

- Technical advisor
- Project management
- Spatial planning, development & management

# Philosophy



# Rail: Oosterheem Line



## Project description

The Oosterheem Line is a new 5 km stretch of light railway linking the Vinex site Oosterheem (20.000 inhabitants) with Zoetermeer, The Hague and Rotterdam.

## Services delivered

Customer: Stadsgebied Haaglanden, city Zoetermeer

Services:

Feasibility study

Engineering

Tender-design

Permits

Assistance during procurement procedure

Contract engineering


Year: 2000 – 2012

# Rail: Oosterheem Line



- 17 multilevel interchanges
- 5 stations
- 1200 metres long viaduct
- 6 metres above ground level
- Geotechnical investigations
- Structural design
- Track alignment
- Power supply
- Communications
- Environmental considerations
- Risk management

# Rail: Oosterheem Line



# Rail: RET Tramplus



## Project description

Tramplus Line Rotterdam – Vlaardingen is partly a renewal of the existing light rail track, as well an entirely new tram track. The alignment is 19 kilometres long. Overhead lines. Stops.

## Services delivered

Customer: Rotterdam Electric Tram (RET)


Services:  
Engineering  
Assistance during procurement procedure  
Contract engineering

Year: 2003 – 2009

# Rail: RET Tramplus



# Rail: Spartacus



## Project description

The Spartacus plan aims to make an important contribution to the improvement of the infrastructure for public transport. The project will be realised via a DBFM procedure.

The current railway connections will be supplemented by three new rapid tram lines, which, together with the existing and new bus lines, are expected to create an efficient network of public transport.

## Services delivered

Customer: Flemish Transportation Company 'De Lijn'  
(The Line)

### Services:

- Environmental impact studies
- Target images
- Project Memoranda
- Reference design
- Performance tender
- Supervision of the tendering procedure

Year: 2007 – 2012

# Rail: Spartacus




# BROL - Grontmij

## Why BROL?

- Makes use of Bentley rail track as basis for the track design.
- It's simple to make cross sections.
- It's simple to make a design check when there is a new track design.
- It's a 3D design that is demanded more and more by the customer.
- You can extract lists with quantities.
- In the future BROL can be connected to Staad-Pro, in order to make the construction calculations.


# BROL - Grontmij

- The software has been designed so that it can be modified for use anywhere in the world. The contents of the design are contained within a Microsoft Access database to which items can be added and results extracted
- This software structure is illustrated on the diagram below:



# BROL - Grontmij

- Bentley developed a work flow process which has been adopted for the software menu structure and is shown on the following diagram:



# BROL - Grontmij

## What has been done so far?

- Dutch Overhead Line system has been talked through with Bentley.
- Algorithms from BROL have been investigated.
- The algorithms of the Dutch Overhead Line system calculations have been determined
- Dutch drawing specification has been submitted.

# BROL - Grontmij

## EXISTING BROL CONFIGURABLE PARAMETERS

- Wire System
- Wire Span Lengths
- Stagger Calculations
- Height Calculations

# BROL - Grontmij

## Additional Requirements for BROL Select series 1

Looking at the requirements for the B1 and B4 systems there are four new basic requirements that must be added to the algorithms and rules embedded in the current version of BROL.


These are:

- Snow loading.
- Pantograph width.
- Temperature.
- Wind speed defined by location.

# BROL - Grontmij

## B1 System Tensioning Arrangements


The B1 type consists of three wires and is known as the “Classical” system where the carrier and catenary wires are fixed between the posts and the contact wire is tensioned (see diagram below):



# BROL - Grontmij

## B4 System Tensioning Arrangements

The B4 is usually used on high speed lines and is known as the “Moving” system. It too is a three wire system, however the contact and carrier wires are tensioned in this system (see diagram below):



# BROL - Grontmij

## Wind Blow Off Formula

The blow off value at a particular location is calculated from:

Abbreviation	Description
q L H Formula	Wind pressure ( $\text{N/m}^2$ ) Span length (m) Tension (N) $U_{\max}$ (maximum wind blow off)


### Formules:

$$U_{\max} = \frac{q \cdot L^2}{8 \cdot H}$$
$$U_a = \frac{4 \cdot a \cdot f_{\max} (L_1 - a)}{L^{12}}$$

# BROL - Grontmij

## Carrier Wire Sag

The formula calculates the maximum distance from the theoretical horizontal plane and perpendicular to it.



Formules:

$$f_{max} = \frac{q \cdot L^2}{8 \cdot H} + \frac{h}{2} \cdot \left(1 + \frac{H \cdot h}{q \cdot L^2}\right)$$

$$fa = \frac{4 \cdot a \cdot f_{max} (L_1 - a)}{L_1^2}$$

$$\frac{L_1}{2} = \frac{L}{2} + \frac{H \cdot h}{q \cdot L}$$

$$dL_k = L_k \cdot a \cdot D_t$$

$$\frac{q_{12} \cdot L_2}{24 \cdot H_{12}} - \frac{q_{22} \cdot L_2}{24 \cdot H_{22}} = \frac{H_1}{A \cdot E} - \frac{H_2}{A \cdot E} - a \cdot (t_2 - t_1)$$

$$H = A \cdot E \cdot a \cdot D_t$$

# BROL - Grontmij

## Production Drawings

As stated in the introduction BROL Select series 1 now has specific tools for creating user definable plans and cross sections

[Bentley Rail Solutions\BROL AVIs\BROL BETA Demonstration Files\BROL - Draw Cross Section.wmv](#)

# BROL - Grontmij

New “Assembly” and “Template” tools.  
MicroStation cells used to create “Assemblies”.

[Bentley Rail Solutions\BROL AVIs\BROL](#)  
[BETA Demonstration](#)  
[Files\BuildTemplates.avi](#)

# BROL - Grontmij

What has to be done yet?

- Checking algorithms
- Filling of the library

# BROL - Grontmij

Questions...and conclusions